

	<h2>SPECIFICATION SHEET</h2>	<p>20917 Higgins Court Torrance, Ca. 90501</p> <p>Phone: 310-357-4450 800-444-2288 Fax: 310-357-4465</p> <p>www.main-line-inc.com e-mail: sales@main-line-inc.com engineering@main-line-inc.com</p>
--	------------------------------	--

Factory 862 MHz Cable Simulators for:

Philips 6-2E862/C*L and 7-2E862/C*-WC Series

Value (dB)	Insertion Loss @ MHz							Tilt (dB)
	45	85	450	550	650	750	870	
1.0	0.2	0.3	0.7	0.8	0.8	0.9	1.0	0.8
2.0	0.2	0.4	1.2	1.3	1.5	1.6	1.8	1.6
3.0	0.2	0.4	1.7	1.9	2.1	2.4	2.6	2.4
4.0	0.2	0.5	2.2	2.5	2.8	3.1	3.4	3.2
5.0	0.3	0.7	2.8	3.2	3.6	3.9	4.3	4.0
6.0	0.6	1.1	3.6	4.1	4.5	5.0	5.4	4.8
7.0	0.7	1.3	4.2	4.8	5.3	5.8	6.3	5.6
8.0	0.9	1.5	4.8	5.5	6.1	6.6	7.3	6.4
9.0	1.1	1.8	5.5	6.2	6.9	7.6	8.3	7.2
10.0	1.3	2.1	6.2	7.0	7.8	8.5	9.3	8.0
11.0	1.5	2.4	6.9	7.8	8.6	9.4	10.3	8.8
12.0	1.7	2.7	7.6	8.6	9.5	10.3	11.3	9.6

Return Loss I/O: **16/16 dB**

Passband Flatness: **+/-0.2 dB** cable equivalent

Note: Measurements on individual cable simulators may differ slightly from these values.