

	<h2>SPECIFICATION SHEET</h2>	<p>20917 Higgins Court Torrance, Ca. 90501</p> <p>Phone: 310-357-4450 800-444-2288 Fax: 310-357-4465</p> <p>www.main-line-inc.com e-mail: sales@main-line-inc.com engineering@main-line-inc.com</p>
--	------------------------------	--

Replacement 862 MHz Cable Simulators for:

C-COR Style SCS-862/* Series Manufactured By Mainline

Part Number	Value (dB)	Insertion Loss @ MHz								Tilt (dB)
		50	100	300	450	550	750	806	862	
MCCRE-00	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
MCCRC862-02	2.0	1.0	1.1	1.4	1.6	1.7	1.9	2.0	2.0	1.0
MCCRC862-03	3.0	1.0	1.2	1.9	2.2	2.4	2.8	2.9	3.0	2.0
MCCRC862-04	4.0	1.0	1.3	2.3	2.8	3.2	3.8	3.9	4.0	3.0
MCCRC862-05	5.0	1.0	1.4	2.8	3.5	3.9	4.7	4.9	5.0	4.0
MCCRC862-06	6.0	1.0	1.5	3.2	4.0	4.6	5.5	5.8	6.0	5.0
MCCRC862-07	7.0	1.0	1.6	3.5	4.5	5.2	6.3	6.6	7.0	6.0
MCCRC862-08	8.0	1.0	1.7	4.0	5.3	6.0	7.3	7.6	8.0	7.0
MCCRC862-09	9.0	1.0	1.8	4.3	5.8	6.6	8.1	8.5	9.0	8.0
MCCRC862-10	10.0	1.0	2.0	4.8	6.3	7.3	9.0	9.4	10.0	9.0
MCCRC862-11	11.0	1.0	2.1	5.2	6.9	8.0	10.0	10.3	11.0	10.0
MCCRC862-12	12.0	1.0	2.2	5.7	7.5	8.7	10.9	11.4	12.0	11.0
MCCRC862-13	13.0	1.0	2.3	6.2	8.2	9.5	11.9	12.4	13.0	12.0
MCCRC862-14	14.0	1.0	2.6	6.7	8.7	10.0	12.9	13.4	14.0	13.0
MCCRC862-15	15.0	1.0	2.7	7.2	9.3	10.6	13.7	14.3	15.0	14.0

Return Loss I/O: **18/16 dB** (-02 through -13)
16/16 dB (-14 through -15)

Passband Flatness: **0.4 dB**, Peak to Valley (-02 through -13)
0.6 dB, Peak to Valley (-14 through -15)

Note: Measurements on individual cable simulators may differ slightly from these values.